



JH 10 G plus - hydraulic jack with integrated pump unit

Load capacity: 10 t
Stroke: 150 mm

Art.-Nr. 01 100 102-G

Advantages of jacks – Series JH G plus

- Slide shoe design inside the guiding track prevents twisting of the piston inside the lifting cylinder. This guarantees better force distribution, less friction and reduced wear compared to conventional jacks.
- Reduced maintenance costs due to easy change slide shoes and removable pump unit.
- Extremely lightweight with high performance due to the use of highquality material and innovative design.
- Continuous adjustment to the load due to swiveling safety toe. Secure stableness in every situation even in lifted position.
- JH 15 / JH 20 G plus serial outfitted with fast stroke.
- Die-forged steel toe provides impact resistance.

Here you find an [application video](#).

Technical data

Title	Unit	Data
Load capacity on top plate	kg	10000
Stroke	mm	150
Minimum lift toe height	mm	15
Maximum lift toe height	mm	180
Lift toe adjustment	mm	5 x 41
Top plate height	mm	275
Toe width front	mm	60
Toe depth	mm	55
Length feet in front	mm	346

Title	Unit	Data
Length feet on side	mm	330
Width	mm	247
Height	mm	310
Cylinder volume	L	0,3
Weight	kg	30