



## JH 20 G plus EX - hydraulic jack without integrated pump unit

Load capacity: 20 t

Stroke: 190 mm

Art.-Nr. 11 620 106-G

### Advantages of jacks – Series JH G plus EX

- Integrated spring return retracts piston automatically on JH 15 up to JH 30 G plus EX.
- Slide shoe design inside the guiding track prevents twisting of the piston inside the lifting cylinder. This guarantees better force distribution, less friction and reduced wear compared to conventional jacks.
- Reduced maintenance costs due to removable stroke unit and easy to change slide shoes.
- Extremely lightweight with high performance due to the use of high quality material and innovative design.
- Continuous adjustment to the load due to swiveling safety toe. Secure stability in every situation even in lifted position.

Here you find an [application video](#).

## Technical data

Title	Unit	Data
Load capacity	kg	20 000
Stroke	mm	190
Minimum lift toe height	mm	20
Maximum lift toe height	mm	225
Lift toe adjustment	mm	5 x 51
Top plate height	mm	340
Toe width front	mm	80
Toe depth	mm	64
Length feet in front	mm	360

<b>Title</b>	<b>Unit</b>	<b>Data</b>
Length feet on side	mm	330
Width	mm	322
Height	mm	340
Cylinder volume	L	0,73
Weight	kg	52