



## JHS 10 ku - hydraulic jack without pump and hose

Load capacity: 10 t

Stroke: 288 mm

Art.-Nr. 01 020 105-O

### Advantages of jack sets – Series JHS

- 180° revolving housing, this allows the jack to be placed with long or with short feet to the load, if there is no space under that.
- High capacity at low weight.
- Pump unit separated from jack, flexible use, ideal also for confined spaces, also operates in horizontal position.
- Swiveling lifting toe assures optimal adjustment to the load, along with safe and stable support even in raised position.
- Swiveling elbowed nipple allows hose connection from various directions.
- JHS 10 ku as set (JSET 20/3 ku) suits perfectly to the container transport trolleys.

Here you find an [application video](#).

## Technical data

Title	Unit	Data
Load capacity on top plate	kg	10000
Minimum lift toe height	mm	20
Maximum lift toe height	mm	288
Lift toe adjustment	mm	5 x 41
Top plate height	mm	265
Maximum top plate height	mm	373
Toe width front	mm	60
Toe depth	mm	55
Diameter top plate	mm	95
Length toe supported without handle	mm	205

<b>Title</b>	<b>Unit</b>	<b>Data</b>
Length toe exposed without handle	mm	260
Width	mm	200
Cylinder volume	L	0,21
Weight	kg	19