



## JKB 2 Set with JUWathan

Load capacity: 2 x 2 t

Height: 110 mm

Art.-Nr. 14 020 085-DVu

### Advantages of revolving transport trolleys

- Optional connecting bars can be fixed without tools by clamping down on adapter.
- High load capacity at low weight.
- Bearing supported swiveling castors allow 360° maneuverability.
- Mix and match revolving trolleys with transport trolleys: With an installation height of only 110 mm\*, the rotating transport trolley JKB 2 is compatible with all steering and transport undercarriages of the K series.
- All products are also available in a set of two with price advantage.
- Unrivalled: The double roller system reduces rolling and turning resistance to a minimum.
- In addition, all the rotational trolleys have a platform center hole to allow attachment to the load.
- For choosing the adequate revolving trolley we recommend a load of two-third of the maximum capacity. This will be the most advantageous compromise between payload, ergonomics and handling of the devices.
- Pulling handle and connecting bars available as accessories.
- Inspected according to technical regulation ANSI ? ASME (USA)

Here you find an [application video](#).

\*) Due to technical changes, there may be tolerances of up to + 4.5 mm in the installation height since 2014.

## Technical data

Title	Unit	Data
Consist of		2 x JKB 2 K
Load capacity	kg	2 x 2000
Number of castors	pcs.	2 x 6
Castor dimensions Ø x Fitting	mm	85 x 43

<b>Title</b>	<b>Unit</b>	<b>Data</b>
length		
Height	mm	110
Supporting surface of turntable Ø	mm	150
Cassette dimensions	mm	528 x 495
Weight with JUWathan®	kg	40