



JLA-e 15/30 G facelift with stroke

Load capacity: 15 t

Height: 200 mm

Art.-Nr. 22 015 210-G Hub

Advantages of electric-powered transport trolleys with stroke

- Maximum stroke of 50 mm.
- The load can be moved when fully extended.
- No separate towing vehicle is required.
- Compact and practical, with battery operation and a user-friendly wireless remote control. Based on 2.4 GHz technology, equipped with a wired connection socket, allowing for one- or two-handed operation, vibration feedback, and other features.
- Long runtime (under full load in ideal conditions) of approximately 4-5 hours due to a direct-drive motor.
- The new generation of drives prevents rolling, even when powered off.
- The new battery display shows various parameters in real time, such as voltage, current, or charge status.
- Short charging time for the self-propelled transport unit JLA-e 15/30 G.
- Rotatable by 360°.
- Stepless speed control.
- Compact external dimensions.
- The electric transport trolley is compatible with the G series trolleys (adjusted installation height). These are not included in the delivery.
- The advanced LiFePo4 cell technology, with higher energy density, allows for a more compact design.
- Side cover plates with JUNG branding provide dirt protection and a visually appealing design.

Technical data

Title	Unit	Data
Load capacity	kg	15 000
Pulling capacity	kg	30 000
Number of castors	pcs.	16

Title	Unit	Data
Castor dimensions Ø x Fitting length	mm	140 x 59
Height	mm	200
Stroke maximum	mm	50
Supporting surface of turntable Ø	mm	215
Length	mm	1 090 x 1 205
Weight with battery	kg	330
Speed	m/min	6,5
Operational time	h	5-6
Battery and charger	pcs.	1 x
Remote control, charger and belt with holder	pcs.	1 x