



JLA-e 25 ? 50 H facelift

Load capacity: 25 t

Height: 230 mm

Art.-Nr. 22 025 200-H

Advantages of electric-powered transport trolleys

- No separate towing vehicle required.
- Convenient, with battery and handy remote control! Based on 2.4 GHz, with a cable connection port, single or dual-hand operation, vibration feedback, etc.
- High runtime (under full load in ideal conditions) thanks to a directly driven motor. Transport trolley JLA-e 25/50 H: approx. 2-3 hours.
- The new generation of drives prevents rolling away, even when switched off.
- The new battery indicator displays various parameters in real-time, such as voltage, current, or state of charge.
- Short charging time due to an optimized charger. Charging time for the JLA-e 25/50 H transport trolley: approx. 3-4 hours.
- 360° rotatable.
- Infinitely variable speed control.
- The advanced LiFePo4 cell technology with higher energy density allows for a more compact design.
- Compatible with the G series castors. The trolleys are not included in the delivery.
- Also available with lift. See here.
- Side cover plates with JUNG lettering provide dirt protection and an attractive design.
- Tested according to DGUV V68 (D).

Here you find an [application video](#).

Technical data

Title	Unit	Data
Load capacity	kg	25000
Pulling capacity	kg	50000
Number of castors	pcs.	16
Castor dimensions Ø x Fitting length	mm	200 x 83

Title	Unit	Data
Height	mm	230
Supporting surface of turntable Ø	mm	250
Length	mm	1180 x 1760
Weight without battery + controller	kg	593
Weight battery + box	kg	90
Weight charger	kg	16
Speed	m/min	10
Operational time	h	3-4
Battery and charger	pcs.	1x
Remote control, charger and belt with holder	pcs.	1x