



JLA-e 5 / 12 G facelift

Load capacity: 5 t

Height: 180 mm

Art.-Nr. 22 005 200-G

Advantages of Electric Powered Transport Trolleys

- No separate towing vehicle required.
- Convenient, with battery and handy remote control! Based on 2.4 GHz, with a cable connection port, single or dual-hand operation, vibration feedback, etc.
- High runtime (under full load in ideal conditions) thanks to a directly driven motor. Transport trolley JLA-e 5/12 G: approx. 4-5 hours.
- The new generation of drives prevents rolling away, even when switched off.
- The new battery indicator displays various parameters in real-time, such as voltage, current, or state of charge.
- Short charging time due to an optimized charger. Charging time for the JLA-e 5/12 G transport trolley: approx. 3-4 hours.
- 360° rotatable.
- Infinitely variable speed control.
- The advanced LiFePo4 cell technology with higher energy density allows for a more compact design.
- Compatible with the G series castors. The trolleys are not included in the delivery.
- Also available with lift. See [here](#).
- Side cover plates with JUNG lettering provide dirt protection and an attractive design.
- Tested according to DGUV V68 (D).

Here you can find an [application video](#).

Technical data

Title	Unit	Data
Load capacity	kg	5000
Pulling capacity	kg	12000
Number of castors	pcs.	4
Castor dimensions Ø x Fitting	mm	140 x 59

Title	Unit	Data
length		
Height	mm	180
Supporting surface of turntable Ø	mm	150
Cassette dimensions	mm	760 x 880
Weight without battery + controller	kg	136
Weight battery + box	kg	36
Weight charger	kg	3
Speed	m/min	10
Operational time	h	3-4
Battery and charger	pcs.	1x
Remote control, charger and belt	pcs.	1x
with holder		