

Adjustable trolley JFB 6 K

High-performance transport trolley from JUNG. The JFB 6 K trolley transports loads up to 6 t with an installation height of 110 mm.

Product number 08 061 085-V

Weight 25kg



Product description

Advantages of the transport trolley JFB 6 K

- Equipped with highest quality castors as standard.
- Reduced weight due to advanced construction of load cassettes.
- All transport trolleys are ready for use: The adjustable-width transport trolley consists of two transport units and connecting bar.
- Inspected according to technical regulation ANSI ? ASME (USA)

The transport trolleys have a low installation height of 110 mm, making them suitable for almost any load. They are equipped with ball bearing supported rollers that enable effortless maneuvering and positioning. These rollers come with a wear-resistant coating called "JUWathan plus" coating, which ensures a smooth and quiet operation. The transport trolleys are available with an optional handle or towing eye.

Product properties

Number of castors (Pieces)	2 x 4
Castor dimensions (Ø x l mm)	85 x 85
Load capacity (t)	6
Height (mm)	110
Supporting surface per cassette (mm)	170 x 170
Cassette dimensions (mm)	325 x 200
Load capacity (suitable)	11 - 15 t
Connecting bar with joint (mm)	1 230
Cassettes adjustable from - to (mm)	400 - 1 030
Weight JUWathan®plus (kg)	25

More images

