

# Adjustable trolley JFB 6 K

High-performance transport trolley from JUNG. The JFB 6 K trolley transports loads up to 6 t with an installation height of 110 mm.

**Product number** 08 061 085-V

**Weight** 25kg



## Product description

Advantages of the transport trolley JFB 6 K

- Equipped with highest quality castors as standard.
- Reduced weight due to advanced construction of load cassettes.
- All transport trolleys are ready for use: The adjustable-width transport trolley consists of two transport units and connecting bar.
- Inspected according to technical regulation ANSI ? ASME (USA)

The transport trolleys have a low installation height of 110 mm, making them suitable for almost any load. They are equipped with ball bearing supported rollers that enable effortless maneuvering and positioning. These rollers come with a wear-resistant coating called "JUWathan plus" coating, which ensures a smooth and quiet operation. The transport trolleys are available with an optional handle or towing eye.

## Product properties

<b>Number of castors (Pieces)</b>	2 x 4
<b>Castor dimensions (Ø x l mm)</b>	85 x 85
<b>Load capacity (t)</b>	6
<b>Height (mm)</b>	110
<b>Supporting surface per cassette (mm)</b>	170 x 170
<b>Cassette dimensions (mm)</b>	325 x 200
<b>Load capacity (suitable)</b>	11 - 15 t
<b>Connecting bar with joint (mm)</b>	1 230
<b>Cassettes adjustable from - to (mm)</b>	400 - 1 030
<b>Weight JUWathan®plus (kg)</b>	25

More images

