

## JH 6 G plus - Hydraulic jack

High-quality jack from JUNG. The hydraulic lifting device JH 6 G plus lifts a load of 6 t and reaches a maximum lifting height of 140 mm.

<b>Product number</b>	01 060 102-G
<b>Weight</b>	22kg
<b>Width</b>	233mm
<b>Height</b>	280mm



### Product description

Advantages of the hydraulic jack JH 6 G plus

- Slide shoe design inside the guiding track prevents twisting of the piston inside the lifting cylinder. This guarantees better force distribution, less friction and reduced wear compared to conventional jacks.
- Reduced maintenance costs due to easy change slide shoes and removable pump unit.
- Extremely lightweight with high performance due to the use of highquality material and innovative design.
- Continuous adjustment to the load due to swiveling safety toe. Secure stability in every situation even in lifted position.
- JH 15 / JH 20 G plus serial outfitted with fast stroke.
- Die-forged steel toe provides impact resistance.

## Product properties

<b>Toe width front (mm)</b>	50
<b>Maximum lift toe height (mm)</b>	157
<b>Length feet on side (mm)</b>	311
<b>Lift toe adjustment</b>	6 x 29
<b>Load capacity on top plate (t)</b>	6
<b>Stroke (mm)</b>	140
<b>Minimum lift toe height (mm)</b>	12
<b>Width (mm)</b>	233
<b>Length feet in front (mm)</b>	326
<b>Cylinder volume (l)</b>	0,18
<b>Top plate height (mm)</b>	245
<b>Pump unit included</b>	Ja
<b>Toe depth (mm)</b>	50
<b>Height (mm)</b>	280

More images



