

JH 6 G plus - Hydraulic jack

High-quality jack from JUNG. The hydraulic lifting device JH 6 G plus lifts a load of 6 t and reaches a maximum lifting height of 140 mm.

Product number 01 060 102-G

Weight 22kg

Width 233mm

Height 280mm



Product description

Advantages of the hydraulic jack JH 6 G plus

- Slide shoe design inside the guiding track prevents twisting of the piston inside the lifting cylinder. This guarantees better force distribution, less friction and reduced wear compared to conventional jacks.
- Reduced maintenance costs due to easy change slide shoes and removable pump unit.
- Extremely lightweight with high performance due to the use of highquality material and innovative design.
- Continuous adjustment to the load due to swiveling safety toe. Secure stability in every situation even in lifted position.
- JH 15 / JH 20 G plus serial outfitted with fast stroke.
- Die-forged steel toe provides impact resistance.

Product properties

Toe width front (mm)	50
Maximum lift toe height (mm)	157
Length feet on side (mm)	311
Lift toe adjustment	6 x 29
Load capacity on top plate (t)	6
Stroke (mm)	140
Minimum lift toe height (mm)	12
Width (mm)	233
Length feet in front (mm)	326
Cylinder volume (l)	0,18
Top plate height (mm)	245
Pump unit included	Ja
Toe depth (mm)	50
Height (mm)	280

More images



