


Revolving transport trolley JKB 2 K Set

Agile and powerful revolving transport trolley from JUNG. The JKB 2 K transport trolley set transports loads up to 4 t with an installation height of 110 mm.

Product number 14 020 085-DVu

Weight 40kg



Product description

Advantages of revolving transport trolleys set JKB 2 K

- Optional connecting bars can be fixed without tools by clamping down on adapter.
- The set consists of two JKB 2 K rotating trolleys.
- High load capacity at low weight.
- Bearing supported swiveling castors allow 360° maneuverability.
- Mix and match revolving trolleys with transport trolleys: With an installation height of only 110 mm*, the rotating transport trolley JKB 2 is compatible with all steering and transport undercarriages of the K series.
- Unrivalled: The double roller system reduces rolling and turning resistance to a minimum.
- In addition, all the rotational trolleys have a platform center hole to allow attachment to the load.
- For choosing the adequate revolving trolley we recommend a load of two-third of the maximum capacity. This will be the most advantageous compromise between payload, ergonomics and handling of the devices.
- Pulling handle and connecting bars available as accessories.
- Inspected according to technical regulation ANSI ? ASME (USA)
- The wheel assemblies are equipped with high-quality JUWATHAN plus casters made of polyurethane. The optimized covering thickness has reduced the rolling resistance and weight. The covering is suitable for moderately contaminated industrial floors with small heels and unevenness.

It is recommended to select a payload of approximately 2/3 of the maximum load capacity to achieve the best compromise between payload, ergonomics, and handling of the equipment.

*) Due to technical changes, there may be tolerances of up to + 4.5 mm in the installation height since 2014.

Product properties

Cassette dimensions (mm)	528 x 495
Castor dimensions (Ø x l mm)	85 x 43
Number of castors (Pieces)	2 x 6
Height (mm)	110
Load capacity (t)	4
Weight JUWathan® (kg)	40
Supporting surface per cassette (mm)	150
Consist of	2 x JKB 2 K

More images

