

# Revolving transport trolley JKB 6 K Set

Agile and powerful revolving transport trolley from JUNG. The JKB 6 K transport trolley set transports loads up to 12 t with an installation height of 110 mm.

**Product number** 14 061 085-D

**Weight** 82kg



## Product description

Advantages of the revolving transport trolleys set JKB 6 K with JUWAmid

- The set consists of 2 JKB 6 K revolving transport trolleys.
- Optional connecting bars can be fixed without tools by clamping down on adapter.
- Despite its low weight, the wheel assembly can transport heavy loads.
- The wheel assemblies are equipped with ball bearing swivel casters that allow for a 360-degree rotation.
- Mix and match revolving trolleys with transport trolleys: With an installation height of only 110 mm\*, the rotating transport trolley JKB 6 is compatible with all steering and transport undercarriages of the K series.
- Unrivalled: The double roller system reduces rolling and turning resistance to a minimum.
- Using the slots in the platform, the trolleys JKB 4 - 8 can be affixed to the load with standard tiedown belts.
- In addition, all the rotational trolleys have a platform center hole to allow attachment to the load.
- For choosing the adequate revolving trolley we recommend a load of two-third of the maximum capacity. This will be the most advantageous compromise between payload, ergonomics and handling of the devices.
- Drawbars and connecting rods are available as accessories in various lengths.
- Inspected according to technical regulation ANSI ? ASME (USA)

\*) Due to technical changes, there may be tolerances of up to + 4.5 mm in the installation height since 2014.

## Product properties

<b>Load capacity (t)</b>	12
<b>Supporting surface per cassette (mm)</b>	250
<b>Castor dimensions (Ø x l mm)</b>	85 x 43
<b>Height (mm)</b>	110
<b>Weight JUWAmid (kg)</b>	82
<b>Number of castors (Pieces)</b>	2 x 16
<b>Consist of</b>	2 x JKB 6 K
<b>Cassette dimensions (mm)</b>	675 x 525

### More images



