

Hydraulic jack JH 15 G plus EX

High-quality jack from JUNG. The hydraulic lifting device JH 15 G plus EX lifts a load of 15 t and reaches a maximum lifting height of 175 mm.

Product number 11 615 106-G

Weight 42kg

Width 300mm

Height 310mm



Product description

Advantages of the hydraulic jack JH 15 G plus EX

- without integrated pump unit

- Integrated spring return retracts piston automatically on JH 15 G plus EX.
- Slide shoe design inside the guiding track prevents twisting of the piston inside the lifting cylinder. This guarantees better force distribution, less friction and reduced wear compared to conventional jacks.
- Reduced maintenance costs due to removable stroke unit and easy to change slide shoes.
- Extremely lightweight with high performance due to the use of highquality material and innovative design.
- Continuous adjustment to the load due to swiveling safety toe. Secure stability in every situation even in lifted position.

Product properties

Toe depth (mm)	64
Pump unit included	Nein
Load capacity on top plate (t)	15
Toe width front (mm)	80
Lift toe adjustment	5 x 46
Length feet in front (mm)	340
Width (mm)	300
Minimum lift toe height (mm)	20
Length feet on side (mm)	230
Stroke (mm)	175
Cylinder volume (l)	0,5
Top plate height (mm)	310
Height (mm)	310
Maximum lift toe height (mm)	205

More images



